Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:



1. Identification

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15

Relevant identified uses of the

substance or mixture and uses

advised against:

Other means of identification

Chemical Manufacturer / ITW Evercoat

Importer / Distributor: a division of Illinois Tool Works Inc.

1275 Round Table Drive

Dallas, TX 75247

Emergency telephone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

Automotive reconditioning product

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:

Storage:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Warning

GHS Hazard Statements: May cause respiratory irritation.

GHS Precautionary Statements:

Safety Precautions: Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

First Aid Measures: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

Hazards not otherwise

MEDICAL CONDITIONS AGGRAVATED: dermatitis may be aggravated by excessive

classified: exposure to skin.

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Hyrotreated Heavy Naphthe	68551-16-6	15 - 40

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact: Use an eye wash to remove a chemical from your eye regardless of

the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing. Flush eye with water for 20 minutes. Get medical attention. Seek medical

advice if symptoms persist

Skin Contact: Wash with soap and water. Wash affected area thoroughly with

soap and water.

Inhalation: This material does not present a hazard if inhaled. Remove

individual to fresh air after an airborne exposure if any symptoms develop, as a precautionary measure. If inhaled, remove victim

from exposure to a well-ventilated area.

Ingestion: No hazard in normal industrial use. Do not induce vomiting. Seek

medical attention if symptoms develop. Provide medical care provider with this MSDS. Do not induce vomiting unless directed to do so by medical personnel. Call a physician or poison control

center immediately.

Most important May cause headaches and dizziness.

symptoms/effects (Delayed:

Immediate medical attention and special treatment needed,:

No additional first aid information available

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

5. Fire-fighting measures

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water

spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Regular foam Carbon dioxide Dry

chemical

Unsuitable extinguishing media:

No data available

Fire and/or Explosion Hazards:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition

and flash back.

Hazardous Combustion

Products:

Carbon monoxide, Carbon dioxide

Special protective equipment and precautions for fire-

fighters:

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the

potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water

and burn while floating on the surface.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up: No adverse health affects expected from the clean-up of spilled material. Follow personal protective equipment recommendations

found in Section VIII of this MSDS.

No special spill clean-up considerations. Collect and discard in regular trash. SMALL SPILL: Contain and collect with absorbent. LARGE SPILLS: Shut off leak if safe to do so. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling: No special handling instructions due to toxicity. Keep out of the

reach of children.

Conditions for safe storage: Store in a cool dry place. Isolate from incompatible materials. For

maximum product quality, avoid prolonged storage at

temperatures below 40°F (4°C) or above 95°F (35°C). Shelf life is

one year.

Materials to Avoid/Chemical Incompatibility::

Strong oxidizing agents Strong acids Strong alkalies

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

8. Exposure controls/personal protection

Limits:

Eye Protection:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
No data available			
Appropriate engineering controls.:	No exposure limits exist for the constituents of this product. No engineering controls are likely to be required to maintain operator comfort under normal conditions of use. General or local ventilation or isolation may prove adequate to keep airborne		

Wear safety glasses when handling this product. Safety Glasses or

goggles with splash guards or side shields.

Skin Protection: Not normally considered a skin hazard. Where use can result in skin

exposures below exposure limits.

contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking,

and when leaving work. Use Nitrile/ Vinyl gloves

Respiratory Protection: No respiratory protection required under normal conditions of use.

NIOSH respirator -(organic vapor) in absence of proper

environmental control.

Other Protective Equipment: Safety Glasses or goggles with splash guards or side shields. Use

Nitrile/ Vinyl gloves

General Hygiene Conditions: Keep out of the reach of children.

9. Physical and chemical properties

Appearance (physical state):

Color:

Odor:

Hydrocarbon

No data available

PH:

Melting Point/Freezing Point (°C):

Initial Boiling Point and Boiling Range (°C):

Solid

Yellow

No data available

No data available

No data available

Flash Point (°C): 43

Evaporation Rate: No data available Flammability (solid, gas): No data available **Upper Flammable/Explosive Limit:** No data available Lower Flammable/Explosive Limit: No data available **Vapor Pressure:** No data available **Vapor Density:** No data available **Relative Density:** Not determined Solubility(ies): No data available Partition coefficient: n-octanol/water: No data available

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

Auto-ignition Temperature (°C):No data availableDecomposition Temperature::No data availableViscosity:No data available

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions. **Conditions to avoid:** None known. Contamination.

Incompatible materials: Strong oxidizing agents Strong acids Strong alkalies

Hazardous decomposition

products:

Carbon dioxide Carbon monoxide

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and

eye contact):

Skin contact, Eye contact, Ingestion

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: No hazard in normal industrial use. Irritating to the nose, throat, and respiratory

tract.

Skin Contact: No hazard in normal industrial use.

Skin Absorption: No absorption hazard in normal industrial use. Contact with skin can cause

irritation, (minor itching, burning and /or redness), Dermatitis, Defatting may be

readily absorbed through the skin.

Eye Contact: Can cause minor irritation, tearing and reddening. Can cause moderate irritation.

Ingestion Irritation: No hazard in normal industrial use. Harmful if swallowed.

Ingestion Toxicity:

Long-Term (Chronic) Health Effects:

Carcinogenicity:None of the substances have been shown to cause cancer in long term animal

studies. Not a carcinogen according to NTP, IARC, or OSHA.

Reproductive andNo data available to indicate product or any components present at greater than

Developmental Toxicity: 0.1% may cause birth defects.

Mutagenicity:No data available to indicate product or any components present at greater than

0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, no hazard in normal industrial use.

Skin Contact: Unlikely to cause irritation even on repeated contact.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50	
No data available				

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
No data available				

12. Ecological information

Ecotoxicity (aquatic and

This material is not expected to be harmful to the ecology.

terrestrial, where available):

Persistence and degradability: No data available No data available Other adverse effects (such as No data available

Other adverse effects (such as hazardous to the ozone layer):

Données sur l'écotoxicité

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues:Spent or discarded material is a hazardous waste.
Disposal must be in accordance with applicable Federal,

State/Provincial and Local regulations.

Waste treatment methods

Dispose of by incineration following Federal, State, Local, or

(including packaging):

Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN number: UN1263
UN proper shipping name: Paint
Transport hazard class(es): 3
Packing group: III

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

Product Name: E-Z WAX PASTE YELLOW 13 O

Product identifier: 15 Revision Date: 12-14-2015

Replaces:

15. Regulatory information

Statut TSCA: All chemicals in this product are listed, or are exempt from

listing on the TSCA Inventory.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
No data available					

16. Other information, including date of preparation or last revision.

Revision Date: 12-14-2015

Revision Number: 10

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances