



# Safety Data Sheet

Issue date 06-Aug-2018

Revision date 08-Nov-2022

Revision Number 2

## 1. IDENTIFICATION

### Product identification

Product identifier Kent® Brushable White Seam Sealer

Other means of identification P10120

Recommended use Adhesive, Sealant

Restrictions on use For industrial use only

### Supplier

Corporate Headquarters:  
Kent Automotive  
8770 W. Bryn Mawr Ave.- Suite 900  
Chicago, IL 60631  
(888)-937-5368

Canadian Distribution Center:  
Lawson Canada  
7315 Rapistan Court  
Mississauga, ON L5N 5Z4  
(800) 323-5922

**24 Hour Emergency Phone Number** (888) 426-4851 (Prosar)

**Website** [www.lawsonproducts.com](http://www.lawsonproducts.com)

## 2. HAZARD(S) IDENTIFICATION

**Hazard Classification** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

### Symbol



<b>Signal word</b>	DANGER
<b>Hazard statements</b>	H225 - Highly flammable liquid and vapor H315 - Causes skin irritation H319 - Causes serious eye irritation H340 - May cause genetic defects H350 - May cause cancer H361 - Suspected of damaging fertility or the unborn child H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure H362 - May cause harm to breast-fed children
<b>Precautionary statements</b>	
<b>Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment P260 - Do not breathe dust/fume/gas/mist/vapors/spray P280 - Wear protective gloves/protective clothing and eye/face protection P240 - Ground/bond container and receiving equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P270 - Do not eat, drink or smoke when using this product P263 - Avoid contact during pregnancy/while nursing
<b>Response</b>	
<b>General</b>	P321 - For Specific treatment see section 4 of this sds P308 + P313 - IF exposed or concerned: Get medical advice/attention P312 - Call a POISON CENTER or doctor if you feel unwell
<b>Eyes</b>	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337 + P313 - If eye irritation persists: Get medical advice/attention P314 - Get medical advice/attention if you feel unwell
<b>Skin</b>	P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse
<b>Inhalation</b>	P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P304 + P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
<b>Fire</b>	P370 + P378 - In case of fire: Use carbon dioxide, powder or water spray.
<b>Storage</b>	P405 - Store locked up P403 + P233 - Store in a well-ventilated place. Keep container tightly closed P235 - Keep cool
<b>Disposal</b>	P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable
<b>Hazard(s) Not Otherwise</b>	Not available.

**Classified (HNOC)**

**Physical Hazards Not Otherwise Classified (PHNOC)** Not available.

**Unknown acute toxicity** Not available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Composition** Mixture.

Chemical name	CAS-No	Weight %
Calcium carbonate	1317-65-3	40-60
Toluene	108-88-3	13-30
Solvent naphtha (petroleum), light aliphatic	64742-89-8	5-7
Titanium dioxide	13463-67-7	1.5-5
Fragrance	N/A	1-1.5
Silicon dioxide - hydrated	7631-86-9	<1
Quartz (Crystalline Silica)	14808-60-7	<1
antioxidant	6683-19-8	<1
Anti-Corrosive Agent	27136-73-8	<1
Aluminum Hydroxide	21645-51-2	<1
Wollastonite	13983-17-0	<1
Rubber	25038-32-8	<1
Resin	64365-17-9	<1
RESIN	68648-53-3	<1
Butadiene-Styrene Resin	9003-55-8	<1

The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST-AID MEASURES

**Necessary first-aid measures**

<b>General Information</b>	Immediately remove all soiled and contaminated clothing.
<b>Inhalation</b>	Move to fresh air. Call a physician or Poison Control Center immediately. If unconscious, place patient in side position for transportation.
<b>Ingestion</b>	If symptoms persist, call a physician.
<b>Skin contact</b>	Immediately wash with water and soap and rinse thoroughly.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Most important symptoms (acute)</b>	Not available.
<b>Most important symptoms (over-exposure)</b>	Not available.
<b>Indication of any immediate medical attention and special treatment needed</b>	Not available.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing** Extinguishing powder. Carbon dioxide (CO2). Water spray. Fight larger fires with water

<b>media</b>	spray or alcohol resistant foam.
<b>Unsuitable extinguishing media</b>	Full water jet.
<b>Specific hazards</b>	Formation of toxic gases is possible during heating or in case of fire. In use, may form flammable/explosive vapour-air mixture.
<b>Special protective equipment for fire-fighters</b>	A respiratory protective device may be necessary.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
<b>Methods and materials for containment and cleaning up</b>	Absorb with liquid-binding material (sand, diatomite, universal binders). Ensure adequate ventilation. For waste disposal, see section 13 of the SDS.

## 7. HANDLING AND STORAGE

<b>Precautions for safe handling</b>	Ensure adequate ventilation. Open and handle receptacle with care. Prevent formation of aerosols. Keep away from sources of ignition - No smoking. Protect against electrostatic charges. Keep respiratory protective devices available.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep containers tightly closed and sealed until ready for use. Keep in a dry, cool and well-ventilated place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Chemical name	OSHA PEL (TWA)	California - PELs	ACGIH OEL (TWA)	NIOSH - TWA
Calcium carbonate	15 mg/m <sup>3</sup> TWA 5 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> PEL (respirable fraction, listed under Particulates not otherwise regulated); 10 mg/m <sup>3</sup> PEL (total dust, listed under Particulates not otherwise regulated)		10 mg/m <sup>3</sup> TWA 5 mg/m <sup>3</sup> TWA
Toluene	200 ppm TWA	10 ppm PEL; 37 mg/m <sup>3</sup> PEL	20 ppm TWA	100 ppm TWA 375 mg/m <sup>3</sup> TWA
Solvent naphtha (petroleum), light aliphatic	-			
Titanium dioxide	15 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> PEL (respirable fraction, listed under Particulates not otherwise regulated); 10 mg/m <sup>3</sup> PEL (total dust, listed under Particulates not otherwise regulated)	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	2.4 mg/m <sup>3</sup> TWA 0.3 mg/m <sup>3</sup> TWA
Fragrance	-			
Silicon dioxide - hydrated	20 mppcf TWA 50 µg/m <sup>3</sup> TWA	6 mg/m <sup>3</sup> PEL (total dust); 3 mg/m <sup>3</sup> PEL (respirable fraction)		6 mg/m <sup>3</sup> TWA
Quartz (Crystalline Silica)	50 µg/m <sup>3</sup> TWA	0.05 mg/m <sup>3</sup> PEL (total dust); 0.1 mg/m <sup>3</sup> PEL (respirable dust)	0.025 mg/m <sup>3</sup> TWA	0.05 mg/m <sup>3</sup> TWA
antioxidant	-			
Anti-Corrosive Agent	-			

Chemical name	OSHA PEL (TWA)	California - PELs	ACGIH OEL (TWA)	NIOSH - TWA
Aluminum Hydroxide	-		1 mg/m <sup>3</sup> TWA	
Wollastonite	15 mg/m <sup>3</sup> TWA 5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> PEL (natural and synthetic, total dust, listed under Particulates not otherwise regulated); 5 mg/m <sup>3</sup> PEL (natural and synthetic, respirable fraction, listed under Particulates not otherwise regulated)	1 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA 5 mg/m <sup>3</sup> TWA
Rubber	-			
Resin	-			
RESIN	-			
Butadiene-Styrene Resin	-			

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Individual protection measures, such as personal protective equipment

#### Eye protection

ANSI approved safety goggles are recommended if exposure is likely. An eye wash station should be available.

#### Skin and body protection

Wear chemical resistant gloves (nitrile) and paint suits. The most suitable glove must be chosen in consultation with the gloves supplier who can inform about the breakthrough time of the glove material. Wear suitable gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

#### Respiratory protection

Wear a NIOSH approved organic vapor respirator. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air purifying respirators may not provide adequate protection.

#### Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of workday. Avoid contact with skin, eyes and clothing.

### Canadian Province Occupational Exposure Limits

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
Calcium carbonate	10 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA 3 mg/m <sup>3</sup> TWA	-	10 mg/m <sup>3</sup> TWA	-	-	-	-	10 mg/m <sup>3</sup> TWA TWA EV	10 mg/m <sup>3</sup> TWA
Toluene	50 ppm TWA 188 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m <sup>3</sup> TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA TWA EV 188 mg/m <sup>3</sup> TWA EV	50 ppm TWA
Solvent naphtha (petroleum), light aliphatic	-	-	-	-	-	-	-	-	-	-
Titanium dioxide	10 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA 3 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA	0.2 mg/m <sup>3</sup> TWA 2.5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA TWA EV	10 mg/m <sup>3</sup> TWA
Fragrance	-	-	-	-	-	-	-	-	-	-
Silicon dioxide - hydrated	-	4 mg/m <sup>3</sup> TWA 1.5 mg/m <sup>3</sup>	-	3 mg/m <sup>3</sup> TWA 10 mg/m <sup>3</sup>	-	-	-	-	6 mg/m <sup>3</sup> TWA TWA EV	10 mg/m <sup>3</sup> TWA 3 mg/m <sup>3</sup>

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
		TWA		TWA						TWA
Quartz (Crystalline Silica)	0.025 mg/m <sup>3</sup> TWA	0.025 mg/m <sup>3</sup> TWA	0.025 mg/m <sup>3</sup> TWA	0.1 mg/m <sup>3</sup> TWA	0.025 mg/m <sup>3</sup> TWA	0.025 mg/m <sup>3</sup> TWA	0.10 mg/m <sup>3</sup> TWA	0.025 mg/m <sup>3</sup> TWA	0.1 mg/m <sup>3</sup> TWAEV	0.05 mg/m <sup>3</sup> TWA
antioxidant	-	-	-	-	-	-	-	-	-	-
Anti-Corrosive Agent	-	-	-	-	-	-	-	-	-	-
Aluminum Hydroxide	-	1.0 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	-	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	-	-
Wollastonite	10 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> TWAEV 5 mg/m <sup>3</sup> TWAEV 10 mg/m <sup>3</sup> TWAEV	10 mg/m <sup>3</sup> TWA
Rubber	-	-	-	-	-	-	-	-	-	-
Resin	-	-	-	-	-	-	-	-	-	-
RESIN	-	-	-	-	-	-	-	-	-	-
Butadiene-Styrene Resin	-	-	-	-	-	-	-	-	-	-

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Odor	Characteristic
Odor threshold	Not applicable
pH	Not applicable
Melting point/range °C	Not available
Melting point/range °F	Not available
Boiling point/range °C	110 °C
Boiling point/range °F	230 °F
Flash point °C	7
Flash point °F	44.6
Flash point method used	Not available
Evaporation rate	Not available
Flammability (Solid, Gas)	Not available
Lower explosion limit	1.2 %
Upper explosion limit	7.0 %
Vapor pressure	29 hPa
Vapor density	Not available
Relative density	1.84334
Solubility	Insoluble in water
Partition coefficient	Not available

**(n-octanol/water)****Autoignition temperature °C** Product is not self-igniting**Autoignition temperature °F** Product is not self-igniting**Decomposition temperature °C** Not available**Decomposition temperature °F** Not available**Viscosity** Not available**10. STABILITY AND REACTIVITY****Reactivity** Not applicable.**Chemical stability** Stable.**Possibility of hazardous reactions** Not available.**Conditions to avoid** Not available.**Incompatible materials** No further relevant information available.**Hazardous decomposition products** None known based on information supplied.**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure** Dermal. Eyes.**Symptoms** Causes irritation to the mucous membranes. Irritating to eyes and skin.**Delayed and immediate effects as well as chronic effects from short and long-term exposure** May damage fertility or the unborn child.**Numerical measures of toxicity**

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Calcium carbonate	no data available	-	6450 mg/kg ( Rat )
Toluene	12.5 mg/L/4h (Rat)	8390 mg/kg (Rabbit)	636 mg/kg (Rat)
Solvent naphtha (petroleum), light aliphatic	-	= 5000 mg/kg Mouse 3000 mg/kg Rabbit	5000 mg/kg Mouse = 3000 mg/kg Rabbit
Titanium dioxide	5.09 mg/L Rat	> 10000 mg/kg Rat	>10000 mg/kg Rat
Fragrance	-	-	-
Silicon dioxide - hydrated	>58.8 mg/L Rat	> 2000 mg/kg ( Rabbit )	> 5000 mg/kg ( Rat )
Quartz (Crystalline Silica)	-	-	-
antioxidant	>1.95 mg/L Rat	> 10250 mg/kg Rat >3160 mg/kg Rabbit	>10250 mg/kg Rat > 3160 mg/kg Rabbit
Anti-Corrosive Agent	-	-	-
Aluminum Hydroxide	-	> 5000 mg/kg Rat	>5000 mg/kg Rat
Wollastonite	-	> 5000 mg/kg Rat	>5000 mg/kg Rat
Rubber	-	-	-
Resin	-	>5000 mg/kg Rabbit	> 5000 mg/kg Rabbit
RESIN	-	>10000 mg/kg Rabbit	> 10000 mg/kg Rabbit
Butadiene-Styrene Resin	-	-	-

**ATEmix (dermal)** Not available

**ATEmix (oral)** Not available

**ATEmix (inhalation-gas)** Not available

**ATEmix (inhalation-vapor)** Not available

**ATEmix (inhalation-dust/mist)** Not available

### Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA Carcinogens	NTP
Calcium carbonate	-	-	-	-
Toluene	A4	Group 3	-	-
Solvent naphtha (petroleum), light aliphatic	-	-	-	-
Titanium dioxide	A3	Group 2B	X	-
Fragrance	-	-	-	-
Silicon dioxide - hydrated	-	Group 1 Group 3	Present	Known carcinogen
Quartz (Crystalline Silica)	A2	Group 1	Present	Known carcinogen
antioxidant	-	-	-	-
Anti-Corrosive Agent	-	-	-	-
Aluminum Hydroxide	A4	-	-	-
Wollastonite	A4	Group 3	-	-
Rubber	-	-	-	-
Resin	-	-	-	-
RESIN	-	-	-	-
Butadiene-Styrene Resin	-	Group 3	-	-

### Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Calcium carbonate	-	-	-	-	-	-
Toluene	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Solvent naphtha (petroleum), light aliphatic	-	-	-	-	-	-
Titanium dioxide	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-
Fragrance	-	-	-	-	-	-
Silicon dioxide - hydrated	-	-	-	-	-	-
Quartz (Crystalline Silica)	A2 - Suspected Human Carcinogen	IARC 1 ACGIH A2	ACGIH A2	-	ACGIH A2	C2 carcinogen
antioxidant	-	-	-	-	-	-
Anti-Corrosive Agent	-	-	-	-	-	-
Aluminum Hydroxide	-	-	ACGIH A4	-	ACGIH A4	-
Wollastonite	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Rubber	-	-	-	-	-	-
Resin	-	-	-	-	-	-
RESIN	-	-	-	-	-	-
Butadiene-Styrene	-	-	-	-	-	-



Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Resin						

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish LC50
Calcium carbonate	-	-
Toluene	=12.5mg/L <i>Pseudokirchneriella subcapitata</i> 72h >433mg/L <i>Pseudokirchneriella subcapitata</i> 96h	11.0 - 15.0mg/L <i>Lepomis macrochirus</i> 96h 14.1 - 17.16mg/L <i>Oncorhynchus mykiss</i> 96h 15.22 - 19.05mg/L <i>Pimephales promelas</i> 96h 5.89 - 7.81mg/L <i>Oncorhynchus mykiss</i> 96h 50.87 - 70.34mg/L <i>Poecilia reticulata</i> 96h = 12.6mg/L <i>Pimephales promelas</i> 96h = 28.2mg/L <i>Poecilia reticulata</i> 96h = 5.8mg/L <i>Oncorhynchus mykiss</i> 96h = 54mg/L <i>Oryzias latipes</i> 96h
Solvent naphtha (petroleum), light aliphatic	=4700mg/L <i>Pseudokirchneriella subcapitata</i> 72h	-
Titanium dioxide	-	-
Fragrance	-	-
Silicon dioxide - hydrated	=440mg/L <i>Pseudokirchneriella subcapitata</i> 72h	= 5000mg/L <i>Brachydanio rerio</i> 96h
Quartz (Crystalline Silica)	-	-
antioxidant	>100mg/L <i>Desmodesmus subspicatus</i> 72h	> 100mg/L <i>Brachydanio rerio</i> 96h
Anti-Corrosive Agent	-	-
Aluminum Hydroxide	-	-
Wollastonite	-	-
Rubber	-	-
Resin	-	-
RESIN	-	-
Butadiene-Styrene Resin	-	-

**Persistence and degradability** Not applicable.

### Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
Calcium carbonate 1317-65-3	1317-65-3	-	-
Toluene 108-88-3	108-88-3	2.73 at 20 °C (at pH 7, ECHA_API) 3.44 at 25 °C (at pH 7, ECHA_API); 3.93 at 20 °C (at pH 7, ECHA_API)	-
Solvent naphtha (petroleum), light aliphatic 64742-89-8	64742-89-8	-	-
Titanium dioxide 13463-67-7	13463-67-7	-	-
Fragrance N/A	N/A	-	-
Silicon dioxide - hydrated 7631-86-9	7631-86-9	-	no bioaccumulation expected

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
Quartz (Crystalline Silica) 14808-60-7	14808-60-7	-	-
antioxidant 6683-19-8	6683-19-8	23 at 25 °C	-
Anti-Corrosive Agent 27136-73-8	27136-73-8	-	-
Aluminum Hydroxide 21645-51-2	21645-51-2	-	-
Wollastonite 13983-17-0	13983-17-0	-	-
Rubber 25038-32-8	25038-32-8	-	-
Resin 64365-17-9	64365-17-9	-	-
RESIN 68648-53-3	68648-53-3	-	-
Butadiene-Styrene Resin 9003-55-8	9003-55-8	-	-

**Mobility in soil**

Not available.

**Other adverse effects**

Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs Danger to drinking water if even extremely small quantities leak into the ground.

### 13. DISPOSAL CONSIDERATIONS

**Disposal information**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Contaminated packaging**

Dispose in accordance with local, state and federal regulations.

### 14. TRANSPORTATION INFORMATION

**Shipping Descriptions****DOT**

ID-No	UN1263
Proper shipping name	Paint
Hazard Class(es)	3
Packing group	II
Special Provisions	LTD QTY

**TDG**

ID-No	UN1263
Proper shipping name	Paint
Hazard Class(es)	3
Packing group	II
Special Provisions	LTD QTY

**IATA**

ID-No	UN1263
Proper shipping name	Paint
Hazard Class(es)	3
Packing group	II
Special Provisions	LTD QTY

**IMDG/IMO**

ID-No	UN1263
Proper shipping name	Paint

<b>Hazard Class(es)</b>	3
<b>Packing group</b>	II
<b>EmS No</b>	F-E, S-E
<b>Marine pollutant</b>	No
<b>Special Provisions</b>	LTD QTY

**Marine Pollutants**

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Calcium carbonate	1317-65-3	-	-	-
Toluene	108-88-3	-	-	-
Solvent naphtha (petroleum), light aliphatic	64742-89-8	-	-	-
Titanium dioxide	13463-67-7	-	-	-
Fragrance	N/A	-	-	-
Silicon dioxide - hydrated	7631-86-9	-	-	-
Quartz (Crystalline Silica)	14808-60-7	-	-	-
antioxidant	6683-19-8	-	-	-
Anti-Corrosive Agent	27136-73-8	-	-	-
Aluminum Hydroxide	21645-51-2	-	-	-
Wollastonite	13983-17-0	-	-	-
Rubber	25038-32-8	-	-	-
Resin	64365-17-9	-	-	-
RESIN	68648-53-3	-	-	-
Butadiene-Styrene Resin	9003-55-8	-	-	-

**Special Precautions**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**15. REGULATORY INFORMATION****State regulations****U.S. state Right-to-Know regulations**

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Calcium carbonate	1317-65-3	X	X	X
Toluene	108-88-3	X	X	X
Solvent naphtha (petroleum), light aliphatic	64742-89-8	-	-	-
Titanium dioxide	13463-67-7	X	X	X
Fragrance	N/A	-	-	-
Silicon dioxide - hydrated	7631-86-9	X	X	X
Quartz (Crystalline Silica)	14808-60-7	X	X	X
antioxidant	6683-19-8	-	-	-
Anti-Corrosive Agent	27136-73-8	-	-	-
Aluminum Hydroxide	21645-51-2	-	-	-
Wollastonite	13983-17-0	X	X	X
Rubber	25038-32-8	-	-	-

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Resin	64365-17-9	-	-	-
RESIN	68648-53-3	-	-	-
Butadiene-Styrene Resin	9003-55-8	-	-	-

**California Prop. 65**

WARNING: This product contains a chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS-No	California Prop. 65
Calcium carbonate	1317-65-3	-
Toluene	108-88-3	Developmental
Solvent naphtha (petroleum), light aliphatic	64742-89-8	-
Titanium dioxide	13463-67-7	Carcinogen
Fragrance	N/A	-
Silicon dioxide - hydrated	7631-86-9	Carcinogen
Quartz (Crystalline Silica)	14808-60-7	Carcinogen
antioxidant	6683-19-8	-
Anti-Corrosive Agent	27136-73-8	-
Aluminum Hydroxide	21645-51-2	-
Wollastonite	13983-17-0	-
Rubber	25038-32-8	-
Resin	64365-17-9	-
RESIN	68648-53-3	-
Butadiene-Styrene Resin	9003-55-8	-

**U.S. Federal Regulations****US EPA SARA 313**

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Calcium carbonate	1317-65-3	-	-
Toluene	108-88-3	1000 lb 454 kg 1 lb 0.454 kg	1.0 %
Solvent naphtha (petroleum), light aliphatic	64742-89-8	-	-
Titanium dioxide	13463-67-7	-	-
Fragrance	N/A	-	-
Silicon dioxide - hydrated	7631-86-9	-	-
Quartz (Crystalline Silica)	14808-60-7	-	-
antioxidant	6683-19-8	-	-
Anti-Corrosive Agent	27136-73-8	-	-
Aluminum Hydroxide	21645-51-2	-	-
Wollastonite	13983-17-0	-	-
Rubber	25038-32-8	-	-
Resin	64365-17-9	-	-
RESIN	68648-53-3	-	-
Butadiene-Styrene Resin	9003-55-8	-	-

**US EPA SARA 311/312  
hazardous categorization**

Not available

## TSCA and Canadian Inventories

Chemical name	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification	DSL	NDSL
Calcium carbonate	X	-	-	X
Toluene	X	-	X	-
Solvent naphtha (petroleum), light aliphatic	X	-	X	-
Titanium dioxide	X	-	X	-
Fragrance	-	-	-	-
Silicon dioxide - hydrated	X	-	X	X
Quartz (Crystalline Silica)	X	-	X	-
antioxidant	X	-	X	-
Anti-Corrosive Agent	X	-	X	-
Aluminum Hydroxide	X	-	X	-
Wollastonite	X	-	X	-
Rubber	X	-	X	-
Resin	X	-	X	-
RESIN	X	-	X	-
Butadiene-Styrene Resin	X	-	X	-

Legend X - Listed

## 16. OTHER INFORMATION

## NFPA

Health	2
Flammability	3
Instability	0

## HMIS

Health	2
Flammability	3
Physical hazards	0

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 06-Aug-2018

Revision date 08-Nov-2022

## Revision note

## Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)  
 ATE (Average Toxicity Estimate)  
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)  
 HMIS (Hazardous Materials Identification System)  
 IARC (International Agency for Research on Cancer)  
 IATA (International Air Transport Association)

IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)  
NFPA (National Fire Protection Association)  
NTP (National Toxicology Program)  
OEL (Occupational Exposure Level)  
OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
PEL (Permissible Exposure Limit)  
TSCA (Toxic Substance Control Act)  
USEPA (United States Environmental Protection Agency)

**Disclaimer**

**The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.**

**End of Safety Data Sheet**