

SAFETY DATA SHEET

1. Identification

Product identifier Ultra Silicone Sealant

Other means of identification

FIR No. 174399

Recommended use Silicone sealant **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company Name Ford Motor Company

Address Attention: MSDS Information, P.O. Box 1899

Dearborn, Michigan 48121

USA

1-800-392-3673 **Telephone MSDS Information** 1-800-448-2063

msds@brownart.com

Emergency telephone

numbers

Poison Control Center: USA and Canada: 1-800-959-3673 INFOTRAC (Transportation): USA and Canada 1-800-535-5053

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards**

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard **OSHA** defined hazards Not classified.

Label elements

None. **Hazard symbol** Signal word None.

Hazard statement Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Avoid release to the environment. Prevention Wash hands after handling. Response

Storage Store away from incompatible materials.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

May be harmful if swallowed. May cause irritation of respiratory tract. May irritate eyes and skin. When the product is exposed to moisture or during curing, 2-butanone oxime may be formed; this classified (HNOC)

substance is toxic and irritates eyes and other mucous membranes.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM CARBONATE		471-34-1	20 - < 30
STEARIC ACID		57-11-4	3 - < 5
Butanone oxime		96-29-7	1 - < 3

FIR No.: 174399 SDS US

Issue Date: 05-14-2015

Chemical name Common name and synonyms CAS number % **ALUMINIUM** 7429-90-5 < 1

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Direct contact with eyes may cause temporary irritation.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

During fire, gases hazardous to health may be formed. Upon decomposition, this product emits

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

and precautions for firefighters

Use water spray to cool unopened containers.

Fire fighting

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid contact with eyes, skin, and clothing. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water. Stop the flow of material, if this is without risk. Prevent product from entering drains. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment, Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910,1000)

Components	Туре	Value	Form
ALUMINIUM (CAS 7429-90-5)	PEL	5 mg/m3	Respirable dust.
•		15 mg/m3	Total dust.
CALCIUM CARBONATE (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.

FIR No.: 174399 SDS US

Issue Date: 05-14-2015

Components	Туре	Value	Form
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
ALUMINIUM (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
STEARIC ACID (CAS 57-11-4)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
ALUMINIUM (CAS 7429-90-5)	TWA	5 mg/m3	Respirable.
		5 mg/m3	Welding fume or pyrophoric powder.
		10 mg/m3	Total
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
US. Workplace Environmental Ex	cposure Level (WEEL) Guides		
Components	Туре	Value	
Butanone oxime (CAS 96-29-7)	TWA	36 mg/m3	
		10 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If

user operations generate a vapor, dust and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended

exposure limits/guidelines.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Suitable chemical protective gloves should be worn when the potential exists for prolonged or

repeated skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Neoprene gloves

are recommended. Nitrile gloves are recommended.

Other Wear suitable protective clothing. Wear appropriate chemical resistant clothing if applicable.

Respiratory protectionIf engineering controls do not maintain airborne concentrations to a level which is adequate to

protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection

Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material

3/7

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Paste.
Color Grey.
Odor Mild.

Odor threshold Not available.

FIR No.: 174399 SDS US

Version: 01
Issue Date: 05-14-2015

рΗ Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point 203.0 °F (95.0 °C) ASTM D56

Evaporation rate Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability limit - upper

Not available.

Not available.

(%)

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure < 5 mm Hg

69.8 °F (21 °C) Vapor pressure temp. Vapor density > 1 (AIR=1)

Relative density 1.47

Relative density temperature 39.2 °F (4 °C)

Solubility(ies)

POLYMERIZES Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

Other information

< 2 % CAM310 VOC (Weight %)

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Acids. Fluorine. Strong oxidizing agents. Water. Incompatible materials

Hazardous decomposition

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons. Nitrogen oxides (NOx). Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact May be irritating to the skin.

Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Version: 01

FIR No.: 174399 SDS US

Issue Date: 05-14-2015

Components **Species** Calculated/Test Results

CALCIUM CARBONATE (CAS 471-34-1)

Acute

Oral

LD50 Mouse 6450 mg/kg

> Rat 6450 mg/kg

STEARIC ACID (CAS 57-11-4)

Acute Oral

LD50 Rat 4.6 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Harmful to aquatic life with long lasting effects. **Ecotoxicity**

Ecotoxicity

Components **Species** Calculated/Test Results ALUMINIUM (CAS 7429-90-5) **Aquatic** Fish LC50

Rainbow trout, donaldson trout (Oncorhynchus mykiss)

0.16 mg/l, 96 hours

Butanone oxime (CAS 96-29-7)

Aquatic

LC50 Fish Fathead minnow (Pimephales promelas) 777 - 914 mg/l, 96 hours

CALCIUM CARBONATE (CAS 471-34-1)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

8.23 STEARIC ACID

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

FIR No.: 174399 SDS US

Issue Date: 05-14-2015

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

<Unspecified>

Not regulated as dangerous goods.

IATA

<Unspecified>

Not regulated as dangerous goods.

IMDG

<Unspecified>

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not applicable.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Nο

chemical

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. **ALUMINIUM** 7429-90-5 < 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

FIR No.: 174399 SDS US

Issue Date: 05-14-2015

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

ALUMINIUM (CAS 7429-90-5)

CALCIUM CARBONATE (CAS 471-34-1)

US. New Jersey Worker and Community Right-to-Know Act

ALUMINIUM (CAS 7429-90-5)

CALCIUM CARBONATE (CAS 471-34-1)

US. Pennsylvania Worker and Community Right-to-Know Law

ALUMINIUM (CAS 7429-90-5)

CALCIUM CARBONATE (CAS 471-34-1)

US. Rhode Island RTK

ALUMINIUM (CAS 7429-90-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

05-14-2015 Issue date

Version # 01

Health: 1 **HMIS®** ratings

Flammability: 1 Physical hazard: 0

Health: 1 NFPA ratings

Flammability: 1 Instability: 0

Preparation Information and

Disclaimer

This document was prepared by FCSD-Toxicology, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical quidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

TA-29 Part number(s)

FIR No.: 174399

Version: 01 Issue Date: 05-14-2015 7/7