SAFETY DATA SHEET

Revision Date 02-Jun-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name

21425 FAST CURE EPOXY PART 1

Other means of identification

Product Code Synonyms

150345E

None

Recommended use of the chemical and restrictions on use

Recommended Use

(Epoxy resin)

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Distributor

ITW Permatex 10 Columbus Blvd. ITW Permatex Canada 35 Brownridge Road, Unit 1

Hartford, CT 06106 USA

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number

1-87-Permatex (877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

May cause an allergic skin reaction Suspected of causing cancer



Appearance Black

Physical state Viscous liquid

Odor Slight

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Harmful to aquatic life with long lasting effects

Unknown acute toxicity

46.33 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ALUMINUM HYDROXIDE	21645-51-2	30 - 60	*
EPOXY RESIN (EPICHLOROHYDRIN, BISPHENOL A)	25085-99-8	30 - 60	*
TITANIUM DIOXIDE	13463-67-7	3 - 7	*
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	25068-38-6	1 - 5	*
EPOXY RESIN	28906-96-9	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact

ICL

Sensitivity to Static Discharge

None. None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Amines

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m³ respirable fraction	-	-
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Viscous liquid

Appearance Odor

Black Slight

Odor threshold

No information available

Property

Values No information available Remarks • Method

Melting point / freezing point

No information available

Boiling point / boiling range

> 260 °C / >500 °F

Flash point

> 204 °C / > 399 °F

Pensky-Martens Closed Cup (PMCC)

Air = 1

Evaporation rate < 1 Butyl acetate = 1 Flammability (solid, gas) No information available

Flammability Limit in Air
Upper flammability limit:
No information available

Lower flammability limit: No information available Vapor pressure 0.03 mm Hg @ 171°F

Vapor density >1
Relative density 1.53
Water solubility Negligible

Solubility in other solvents No information available Partition coefficient No information available Autoignition temperature No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) <1%

Density No information available Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Amines

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg(Rat)	-	-
TITANIUM DIOXIDE	> 10000 mg/kg(Rat)	-	•

13463-67-7			
BISPHENOL	= 11400 mg/kg (Rat)	-	-
A/EPICHLOROHYDRIN BASED			
EPOXY RESIN			
25068-38-6			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

<u>Carcinogenicity</u> The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE	-	Group 2B	-	X
13463-67-7		·		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Lungs, Respiratory system.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5609 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

95.91 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

14. TRANSPORT INFORMATION

DOT

Proper shipping name:

Not regulated

IATA

Proper shipping name:

Not regulated

IMDG

Proper shipping name:

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Not Listed. **ENCS** Not Listed. **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
CARBON BLACK - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE 13463-67-7	X	X	X
BENZYL ALCOHOL 100-51-6	-	X	Х
CARBON BLACK 1333-86-4	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

NFPA Health hazards 2 Flammability 1 Instability 0 HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

02-Jun-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

S Permatex

SAFETY DATA SHEET

Revision Date 02-Jun-2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name 21425 FAST CURE EPOXY PART 2

Other means of identification

Product Code 150445E Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use Epoxy curing agent
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Emergency Overview	
Danger	
Causes skin irritation Causes serious eye irritation Suspected of causing cancer	

Suspected of damaging fertility or the unborn child Causes damage to organs through prolonged or repeated exposure



Appearance Black

Physical state Viscous liquid

Odor Mercaptan

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Toxic to aquatic life with long lasting effects

Unknown acute toxicity

35.405 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ALUMINUM HYDROXIDE	21645-51-2	30 - 60	*
POLYMERCAPTAN CURING AGENT (TSRN 679485-5016p)	_	15 - 40	*
BENZYL ALCOHOL	100-51-6	5 - 10	*
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	5 - 10	*
STYRENE	100-42-5	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up.

Incompatible materials Strong oxidizing agents, Acids, Peroxides, Sodium hypochlorite, Calcium hypochlorite,

Reactive metals

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

C	hemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALUM	INUM HYDROXIDE 21645-51-2	TWA: 1 mg/m³ respirable fraction	-	-
	STYRENE 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m³ (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m³ Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m³ STEL: 100 ppm STEL: 425 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateViscous liquidAppearanceBlackOdorMercaptan

Odor threshold No information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point

No information available
No information available
> 149 °C / 300 °F
> 93 °C / > 200 °F

Evaporation rate < 1 Butyl acetate = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure

No information available
No information available
<5 mm Hg @ 77°F

Vapor density >1 Air = 1

Relative density 1.4

Water solubility Slightly soluble

Solubility in other solvents No information available No information available Partition coefficient No information available Autoignition temperature No information available **Decomposition temperature** Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available No information available **Oxidizing properties**

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 3%

Density No information available No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Peroxides, Sodium hypochlorite, Calcium hypochlorite, Reactive metals

Hazardous Decomposition Products

Carbon oxides Nitrogen oxides (NOx) Amines Ammonia

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Harmful by inhalation.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg (Rat)	-	-
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 8.8 mg/L (Rat)4 h
2,4,6-TRIS(DIMETHYLAMINOMET HYL)PHENOL 90-72-2	= 1000 mg/kg (Rat)	= 1280 mg/kg(Rat)	-
STYRENE 100-42-5	= 1000 mg/kg (Rat)	-	= 11.7 mg/L (Rat)4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
STYRENE	-	Group 2B	Reasonably Anticipated	X
100-42-5		·	,	

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity

May cause adverse liver effects. Contains a known or suspected reproductive toxin.

Central nervous system, Eyes, Liver, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2458 mg/kg
ATEmix (dermal) 6461 mg/kg
ATEmix (inhalation-dust/mist) 8.9 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

88.93 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
BENZYL ALCOHOL	35: 3 h Anabaena variabilis mg/L	460: 96 h Pimephales promelas	23: 48 h water flea mg/L EC50
100-51-6	EC50	mg/L LC50 static 10: 96 h Lepomis	
		macrochirus mg/L LC50 static	
STYRENE	1.4: 72 h Pseudokirchneriella	3.24 - 4.99: 96 h Pimephales	3.3 - 7.4: 48 h Daphnia magna mg/L
100-42-5	subcapitata mg/L EC50 0.72: 96 h	promelas mg/L LC50 flow-through	EC50
	Pseudokirchneriella subcapitata	19.03 - 33.53: 96 h Lepomis	
	mg/L EC50 0.15 - 3.2: 96 h	macrochirus mg/L LC50 static 58.75	
	Pseudokirchneriella subcapitata	- 95.32: 96 h Poecilia reticulata	
	mg/L EC50 static 0.46 - 4.3: 72 h	mg/L LC50 static 6.75 - 14.5: 96 h	
	Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	

mg/L EC50 static	static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
BENZYL ALCOHOL 100-51-6	1.1
STYRENE 100-42-5	2.95

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
STYRENE	Toxic	
100-42-5	Ignitable	

14. TRANSPORT INFORMATION

DOT

UN/ID no 2735

Proper shipping name: Amines, liquid, corrosive, n.o.s, (2,4,6-tris(dimethylaminomethyl)phenol), Limited Quantity

(LQ)

Hazard Class 8 **Packing Group** Ш **Emergency Response Guide** 153

Number

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class ERG Code

9L

IMDG

UN/ID no 2735

Proper shipping name: Amines, liquid, corrosive, n.o.s, (2,4,6-tris(dimethylaminomethyl)phenol), Limited Quantity

(LQ)

Hazard Class

Packing Group III EmS-No F-A, S-B

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Not determined **ENCS** Not determined **IECSC** Not determined Not determined **KECL PICCS** Not determined **AICS** Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
STYRENE - 100-42-5	0.1		
SARA 311/312 Hazard Categories			
Acute health hazard	Yes		
Chronic Health Hazard	Yes		
Fire hazard	No		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
STYRENE 100-42-5	1000 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
STYRENE	1000 lb		RQ 1000 lb final RQ
100-42-5			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CARBON BLACK - 1333-86-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
STYRENE 100-42-5	Х	X	X
CARBON BLACK 1333-86-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

NFPA Health hazards 2 Flammability 1 Instability 0 - HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

02-Jun-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet