MATERIAL SAFETY DATA SHEET

ECP Incorporated HMIS HAZARD RATING 11210 KATHERINE'S CROSSING, SUITE 100 HEALTH WOODRIDGE, IL 60517 FIRE TELEPHONE 630-754-4200 EMERGENCY 800-424-9300 REACTIVITY PERSONAL PROTECTION DATE OF PREPARATION DATE OF REVIEW/UPDATE APRIL 19, 2007 BY TECHNICAL SERVICES _______ SECTION 1 - PRODUCT IDENTIFICATION ITEM NUMBER 1847 ITEM DESCRIPTION PROTECTOR LEATHER & VINYL ENHANCER PRODUCT CLASS INTERIOR DRESSING SECTION 2 - HAZARDOUS INGREDIENTS MAX. % TLV1 INGREDIENT BY WT. CAS NUMBER Listed as IARC, NTP, or OSHA Carcinogen: None SECTION 3 - PHYSICAL CHARACTERISTICS 212F BOILING POINT: VAPOR PRESSURE (mmHg @ 68F) NOT DETERMINED NOT DETERMINED VAPOR DENSITY (AIR=1) COMPLETE SOLUBILITY IN WATER: 1,0+/-0.05 SPECIFIC GRAVITY: % VOLATILE (VOLUME) 83+/-0.2 NOT APPLICABLE MELTING POINT: EVAPORATION RATE (ether=1) CPAQUE WHITE LIQUID, BLAND ODOR APPEARANCE AND ODOR: SECTION 4 - FIRE AND EXPLOSION HAZARD DATA FLASH POINT / METHOD: NONE TO BOIL F / TCC FLAMMABLE LIMITS: LEL: UNKNOWN UEL: UNKNOWN EXTINGUISHING MEDIA: Water fog, dry chemicals or carbon dioxide. SPECIAL FIRE FIGHTING PROCEDURES:

Full protective equipment including self contained breathing apparatus for confined areas.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air. Treat as petroleum fire.

1847/BOOK 16.24

PAGE 1 OF 3

SECTION 5 - HEALTH HAZARD DATA

SYMPTOMS OF OVEREXPOSURE:

EYES: Can cause irritation, redness, blurred vision.

SKIN: Prolonged or repeated contact can cause moderate

irritation, defatting dermatitis and burns.

INHALATION: Excessive breathing of vapors can cause nasal and

respiratory irritation.

INGESTION: Can cause gastrointestinal irritation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE;

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION Remove exposure.

SKIN Wash affected area with soap and water. Remove

contaminated clothing and launder before reuse.

EYES Flush with large amounts of water. Get medical

attention.

IF SWALLOWED No first aid should be needed.

SECTION 6 - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Silicone Dioxide, Carbon oxides and

other products of incomplete

combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 7 - SPILL ()R LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR LEAKED:

Contain spill. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Waste from this product is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

VENTILATION:

Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred.

RESPIRATORY PROTECTION:

If required a properly fitted NTOSH/MSHA approved respirator rated for the hazardous ingredients found in (SECTION 2).

SKIN PROTECTION:

Gloves rated for protection against ingredients in (SECTION 2).

EYE PROTECTION:

Safety glasses with side shields or chemical goggles.

SECTION 9 - PRECAUTHONARY INFORMATION
PRECAUTIONS TO BE TAKEN IN STORING AND HANDLING: Do not smoke. Never wear soaked clothing. Launder or dry-clean before wearing. Affix proper warning labels on containers in accordance with 29CFR 1010.1200
SECTION 10 - REGULATORY INFORMATION
D.O.T. REQUIREMENTS (49CFR 172.101) Not regulated
RQ (REPORTABLE QUANTITY) 49CFR 172.101 COMPONENT RQ (lb.) FOR THIS PRODUCT
None
TSCA (Toxic Substances Control Act) Status The intentional ingredients of this product are listed.
CERCLA RQ - 40CFR 302.4 None
SARA 302 COMPONENTS - 40CFR 355 Appendix A
SECTION 311/312 HAZARD CLASS - 40CFR 370.2 Immediate (X) Reactive () Delayed () Sudden Release of Pressure () Fire ()
SARA 313 COMPONENTS - 40CFR 372.65
WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS) INGREDIENT MAX. % LD50 LC50 BY WT.
AMINOETHYLAMINOPROPYL DIMETHYL SILOXANE 4 unknown unknown
The information contained herein is based on data we believe to be correct. Any use of the product that is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.
1 ACGIH 2 OSHA