# KENT

AUTOMOTIVE A DIVISION OF LAWSON PRODUCTS, INC.

# SAFETY DATA SHEET.

Issuing date 10-Feb-2015 Revision Date 10-Feb-2015 Version 3.01

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name ACRYSOL

Recommended use of the chemical and restrictions on use

Product code P20010M01

<u>Product Type</u> Highly Flammable Liquid and Vapor

Synonyms None

Supplier's details

Recommended Use MULTI-PURPOSE SOLVENT.

Uses advised against

Manufactured For:

Kent Automotive, Division of Lawson Products, Inc. 8770 W. Byrn Mawr Avenue- Suite 900 Chicago, IL 60631-3515 www.kent-automotive.com

Emergency telephone number

Chemical Emergency Phone 888-426-4851

Number

# 2. HAZARDS IDENTIFICATION

#### Classification

| Acute toxicity - Inhalation (Vapors)             | Category 4  |
|--|-------------|
| Skin corrosion/irritation                        | Category 2  |
| Serious eye damage/eye irritation                | Category 2A |
| Carcinogenicity                                  | Category 2  |
| Specific target organ toxicity (single exposure) | Category 3  |
| Aspiration toxicity                              | Category 1  |
| Flammable Liquids                                | Category 2  |

#### GHS Label elements, including precautionary statements

**Emergency Overview** 

#### **DANGER**

#### Hazard Statements

Harmful if inhaled Causes skin irritation Causes serious eye irritation Suspected of causing cancer May cause drowsiness or dizziness May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



**Appearance** Clear Physical state Liquid **Odor** Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrial/ventilating/lighting /equipment.

Use only non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

Keep container tightly closed.

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None

#### Other information

· Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name         | CAS-No     | Weight %* |
|-----------------------|------------|-----------|
| PETROLEUM DISTILLATES | 64742-89-8 | 75-80     |
| XYLENE                | 1330-20-7  | 15-20     |
| ETHYL BENZENE         | 100-41-4   | 1-5       |
| TOLUENE               | 108-88-3   | 0.1-1.0   |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

General advice Avoid contact with eyes, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek

immediate medical attention/advice.

**Skin contact** Wash off immediately with soap and plenty of water . Remove and wash contaminated

clothing before re-use. Get medical attention immediately if symptoms occur.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

**Ingestion** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

# Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. May cause respiratory irritation. Harmful if swallowed. Inhalation

causing Central Nervous System effects. ingestion causing lung damage.

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

# **Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

**Explosion Data** 

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Environmental precautions** 

**Environmental precautions** Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away

from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible products**Store away from strong oxidizers and acids.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

| Chemical Name | ACGIH TLV     | OSHA PEL                              | NIOSH IDLH |
|---------------|---------------|---------------------------------------|------------|
| XYLENE        | STEL: 150 ppm | TWA: 100 ppm                          | -          |
| 1330-20-7     | TWA: 100 ppm  | TWA: 435 mg/m <sup>3</sup>            |            |
|               |               | (vacated) TWA: 100 ppm                |            |
|               |               | (vacated) TWA: 435 mg/m <sup>3</sup>  |            |
|               |               | (vacated) STEL: 150 ppm               |            |
|               |               | (vacated) STEL: 655 mg/m <sup>3</sup> |            |

| ETHYL BENZENE | TWA: 20 ppm | TWA: 100 ppm                          | IDLH: 800 ppm               |
|---------------|-------------|---------------------------------------|-----------------------------|
| 100-41-4      |             | TWA: 435 mg/m <sup>3</sup>            | TWA: 100 ppm                |
|               |             | (vacated) TWA: 100 ppm                | TWA: 435 mg/m <sup>3</sup>  |
|               |             | (vacated) TWA: 435 mg/m <sup>3</sup>  | STEL: 125 ppm               |
|               |             | (vacated) STEL: 125 ppm               | STEL: 545 mg/m <sup>3</sup> |
|               |             | (vacated) STEL: 545 mg/m <sup>3</sup> | _                           |
| TOLUENE       | TWA: 20 ppm | TWA: 200 ppm                          | IDLH: 500 ppm               |
| 108-88-3      |             | (vacated) TWA: 100 ppm                | TWA: 100 ppm                |
|               |             | (vacated) TWA: 375 mg/m <sup>3</sup>  | TWA: 375 mg/m <sup>3</sup>  |
|               |             | (vacated) STEL: 150 ppm               | STEL: 150 ppm               |
|               |             | (vacated) STEL: 560 mg/m <sup>3</sup> | STEL: 560 mg/m <sup>3</sup> |
|               |             | Ceiling: 300 ppm                      |                             |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

**Engineering Measures**Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

**Eve/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

Physical state Liquid Appearance Clear

Appearance Clear Odor Solvent

Color clear Odor Threshold No information available

Property Values Remarks • Methods

PH No information available

Melting/freezing point No information available

Boiling point/boiling range 118.3-150 °C / 245 - 302 °F

Flash Point

14 °C / 57 °F

Based on lowest flashpoint of the products constituent. (based on components)

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limits in Air

upper flammability limit 7.0 % lower flammability limit 0.8 %

Vapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.779
Water solubility negligible

Partition coefficient: n-octanol/waterNo information available
Autoignition temperature

Decomposition temperature

Viscosity

No information available
No information available

**Explosive properties**No information available

**Other information** 

VOC Content(%) 100

# 10. STABILITY AND REACTIVITY

# Reactivity

Stable under recommended storage conditions

#### **Chemical stability**

Stable under recommended storage conditions.

## Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Store away from strong oxidizers and acids.

#### **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known information

**Inhalation** Exposure to high vapour concentrations may cause nervous systems effects such as

headache, nausea, and dizziness.

**Eye contact** May cause slight irritation.

**Skin contact** Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung

damage which may be fatal.

**Component Information** 

| Chemical Name                       | LD50 Oral            | LD50 Dermal              | LC50 Inhalation        |
|-------------------------------------|----------------------|--------------------------|------------------------|
| PETROLEUM DISTILLATES<br>64742-89-8 | -                    | = 3000 mg/kg ( Rabbit )  | -                      |
| XYLENE<br>1330-20-7                 | = 3500 mg/kg ( Rat ) | > 4350 mg/kg ( Rabbit )  | = 29.08 mg/L (Rat) 4 h |
| ETHYL BENZENE<br>100-41-4           | = 3500 mg/kg ( Rat ) | = 15400 mg/kg ( Rabbit ) | = 17.2 mg/L (Rat) 4 h  |
| TOLUENE<br>108-88-3                 | = 2600 mg/kg ( Rat ) | = 12000 mg/kg ( Rabbit ) | = 12.5 mg/L (Rat) 4 h  |

#### Information on toxicological effects

Symptoms Vapors may cause drowsiness and dizziness. Irritating to skin. Prolonged or repeated

exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during

swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Eye damage/irritation Irritating to eyes.

Sensitization No information available. **Germ Cell Mutagenicity** No information available.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

| Chemical Name | ACGIH | IARC     | NTP | OSHA |
|---------------|-------|----------|-----|------|
| XYLENE        | -     | Group 3  | -   | -    |
| 1330-20-7     |       |          |     |      |
| ETHYL BENZENE | A3    | Group 2B | -   | X    |
| 100-41-4      |       |          |     |      |
| TOLUENE       | -     | Group 3  | -   | -    |
| 108-88-3      |       |          |     |      |

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

The ingredients are not reproductive hazards. Specific target organ systemic causes damage to central nervous system and respiratory system.

toxicity (single exposure)

Specific target organ systemic

toxicity (repeated exposure)

**Chronic toxicity** 

Prolonged skin contact may defat the skin and produce dermatitis. **Target Organ Effects** Central nervous system, Eyes, Respiratory system, Skin.

No information available.

May be fatal if swallowed and enters airways. **Aspiration hazard** 

Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 17255 mg/kg ATEmix (dermal) 2315 mg/kg ATEmix (inhalation-dust/mist) 6.3 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

| Chemical Name                       | Toxicity to algae  | Toxicity to fish | Toxicity to microorganisms | Toxicity to daphnia and other aquatic invertebrates |
|-------------------------------------|--|------------------|----------------------------|---|
| PETROLEUM DISTILLATES<br>64742-89-8 | 4700 mg/L EC50<br>Pseudokirchneriella<br>subcapitata 72h | -                | -                          | -   |

|               |                              | T                              |   |                          |
|---------------|------------------------------|--------------------------------|---|--------------------------|
| XYLENE        | -                            | 13.1 - 16.5 mg/L LC50          | - | 0.6 mg/L LC50 Gammarus   |
| 1330-20-7     |                              | Lepomis macrochirus 96h        |   | lacustris 48h 3.82 mg/L  |
|               |                              | flow-through 13.5 - 17.3       |   | EC50 water flea 48h      |
|               |                              | mg/L LC50 Oncorhynchus         |   |                          |
|               |                              | mykiss 96h 2.661 - 4.093       |   |                          |
|               |                              | mg/L LC50 Oncorhynchus         |   |                          |
|               |                              | mykiss 96h static 23.53 -      |   |                          |
|               |                              | 29.97 mg/L LC50                |   |                          |
|               |                              | Pimephales promelas 96h        |   |                          |
|               |                              | static 30.26 - 40.75 mg/L      |   |                          |
|               |                              | ,                              |   |                          |
|               |                              | LC50 Poecilia reticulata 96h   |   |                          |
|               |                              | static 7.711 - 9.591 mg/L      |   |                          |
|               |                              | LC50 Lepomis macrochirus       |   |                          |
|               |                              | 96h static 13.4 mg/L LC50      |   |                          |
|               |                              | Pimephales promelas 96h        |   |                          |
|               |                              | flow-through 19 mg/L LC50      |   |                          |
|               |                              | Lepomis macrochirus 96h        |   |                          |
|               |                              | 780 mg/L LC50 Cyprinus         |   |                          |
|               |                              | carpio 96h semi-static 780     |   |                          |
|               |                              | mg/L LC50 Cyprinus carpio      |   |                          |
|               |                              | 96h                            |   |                          |
| ETHYL BENZENE | 4.6 mg/L EC50                | 11.0 - 18.0 mg/L LC50          |   | 1.8 - 2.4 mg/L EC50      |
|               | , ,                          |                                | - | _                        |
| 100-41-4      | Pseudokirchneriella          | Oncorhynchus mykiss 96h        |   | Daphnia magna 48h        |
|               | subcapitata 72h 438 mg/L     | static 7.55 - 11 mg/L LC50     |   |                          |
|               | EC50 Pseudokirchneriella     | Pimephales promelas 96h        |   |                          |
|               | subcapitata 96h 2.6 - 11.3   | flow-through 9.1 - 15.6 mg/L   |   |                          |
|               | mg/L EC50                    | LC50 Pimephales promelas       |   |                          |
|               | Pseudokirchneriella          | 96h static 32 mg/L LC50        |   |                          |
|               | subcapitata 72h static 1.7 - | Lepomis macrochirus 96h        |   |                          |
|               | 7.6 mg/L EC50                | static 4.2 mg/L LC50           |   |                          |
|               | Pseudokirchneriella          | Oncorhynchus mykiss 96h        |   |                          |
|               | subcapitata 96h static       | semi-static 9.6 mg/L LC50      |   |                          |
|               |                              | Poecilia reticulata 96h static |   |                          |
| TOLUENE       | 422 mg/L FCF0                |                                | _ | F 46 0 92 mg/L FCF0      |
|               | 433 mg/L EC50                | 11.0 - 15.0 mg/L LC50          | - | 5.46 - 9.83 mg/L EC50    |
| 108-88-3      | Pseudokirchneriella          | Lepomis macrochirus 96h        |   | Daphnia magna 48h Static |
|               | subcapitata 96h 12.5 mg/L    | static 14.1 - 17.16 mg/L       |   | 11.5 mg/L EC50 Daphnia   |
|               | EC50 Pseudokirchneriella     | LC50 Oncorhynchus mykiss       |   | magna 48h                |
|               | subcapitata 72h static       | 96h static 15.22 - 19.05       |   |                          |
|               |                              | mg/L LC50 Pimephales           |   |                          |
|               |                              | promelas 96h flow-through      |   |                          |
|               |                              | 5.89 - 7.81 mg/L LC50          |   |                          |
|               |                              | Oncorhynchus mykiss 96h        |   |                          |
|               |                              | flow-through 50.87 - 70.34     |   |                          |
|               |                              | mg/L LC50 Poecilia             |   |                          |
|               |                              | reticulata 96h static 12.6     |   |                          |
|               |                              | mg/L LC50 Pimephales           |   |                          |
|               |                              | promelas 96h static 28.2       |   |                          |
|               |                              | mg/L LC50 Poecilia             |   |                          |
|               |                              | reticulata 96h semi-static 5.8 |   |                          |
|               |                              |                                |   |                          |
|               |                              | mg/L LC50 Oncorhynchus         |   |                          |
|               |                              | mykiss 96h semi-static 54      |   |                          |
|               |                              | mg/L LC50 Oryzias latipes      |   |                          |
|               |                              | 96h static                     |   |                          |

# <u>Persistence and degradability</u> No information available.

# **Bioaccumulation**

No information available.

| Chemical Name | log Pow |
|---------------|---------|
| XYLENE        | 3.15    |
| 1330-20-7     |         |
| ETHYL BENZENE | 3.118   |
| 100-41-4      |         |
| TOLUENE       | 2.65    |
| 108-88-3      |         |

Other adverse effects No information available

#### 13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

DOT Ground UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE),3, PG II

**IATA** 

For packages > 5 L and < 60 L

UN1993, FLAMMABLE LIQUIDS, N.O.S. (PETROLEUM DISTILLATES, XYLENE), 3, PGII

,LTD.QTY. CARGO AIR CRAFT ONLY.

For packages > 60 L

PACKAGE SIZE NOT ACCEPTED FOR AIR TRANSPORT

IMDG UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE),3, PG II

# 15. REGULATORY INFORMATION

#### **International Inventories**

| Chemical Name            | TSCA | DSL/NDSL | EINECS/ELI<br>NCS | ENCS       | IECSC | KECL | PICCS | AICS |
|--------------------------|------|----------|-------------------|------------|-------|------|-------|------|
| PETROLEUM<br>DISTILLATES | X    | Х        | X                 | Not listed | Х     | Х    | Х     | Х    |
| XYLENE                   | Х    | Х        | Х                 | Х          | Х     | Х    | Х     | Х    |
| ETHYL BENZENE            | Х    | Х        | X                 | Х          | Х     | Х    | Х     | Х    |
| TOLUENE                  | Х    | Х        | Х                 | Х          | Х     | Х    | Х     | Х    |

#### Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name            | CAS-No    | Weight %* | SARA 313 - Threshold<br>Values % |
|--------------------------|-----------|-----------|----------------------------------|
| XYLENE - 1330-20-7       | 1330-20-7 | 15-20     | 1.0                              |
| ETHYL BENZENE - 100-41-4 | 100-41-4  | 1-5       | 0.1                              |
| TOLUENE - 108-88-3       | 108-88-3  | 0.1-1.0   | 1.0                              |

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard no
Reactive Hazard no

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

| Chemical Name             | CWA - Reportable<br>Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous<br>Substances |
|---------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| XYLENE                    | 100 lb                         |                        |                           | X                             |
| 1330-20-7                 |                                |                        |                           |                               |
| ETHYL BENZENE<br>100-41-4 | 1000 lb                        | X                      | X                         | X                             |
| TOLUENE                   | 1000 lb                        | X                      | X                         | X                             |
| 108-88-3                  |                                |                        |                           |                               |

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ                               |
|---------------|--------------------------|------------------------------------|----------------------------------|
| XYLENE        | 100 lb                   |                                    | RQ 100 lb final RQ               |
| 1330-20-7     |                          |                                    | RQ 45.4 kg final RQ              |
| ETHYL BENZENE | 1000 lb                  |                                    | RQ 1000 lb final RQ              |
| 100-41-4      |                          |                                    | RQ 454 kg final RQ               |
| TOLUENE       | 1000 lb 1 lb             |                                    | RQ 1000 lb final RQ              |
| 108-88-3      |                          |                                    | RQ 454 kg final RQ RQ 1 lb final |
|               |                          |                                    | RQ                               |
|               |                          |                                    | RQ 0.454 kg final RQ             |

# U.S. State Regulations

# California Proposition 65

This product contains the following Proposition 65 chemicals:

| Chemical Name            | California Prop. 65 |  |
|--------------------------|---------------------|--|
| ETHYL BENZENE - 100-41-4 | Carcinogen          |  |
| TOLUENE - 108-88-3       | Developmental       |  |
|                          | Female Reproductive |  |

# U.S. State Right-to-Know Regulations

| Chemical Name                       | New Jersey | Massachusetts | Pennsylvania |
|-------------------------------------|------------|---------------|--------------|
| PETROLEUM DISTILLATES<br>64742-89-8 |            |               | X            |
| XYLENE<br>1330-20-7                 | X          | X             | X            |
| ETHYL BENZENE<br>100-41-4           | X          | X             | X            |
| TOLUENE<br>108-88-3                 | X          | X             | Х            |

EPA Pesticide Registration Number Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

B2 Flammable liquid D2B Toxic materials



# **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2\* Flammability 3 Physical Hazard 0 Personal protection B
Chronic Hazard Star Legend Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage

Aromatic solvents Severe overexposure may cause liver or kidney damage

Prepared By Regulatory Affairs Issuing date 10-Feb-2015 Revision Date 10-Feb-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**