

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

1 Identification

Product identifier

Trade name: 824

Other Means of Identification: Isopropyl Alcohol: Electronics Cleaner

CAS Number:

67-63-0

Related Part Number:

824-Liquid, 824-100ML, 824-500ML, 824-1L, 824-4L, 824-20L, 824-205L, 824-1G, 824-100MLCA, 824-1LCA, 824-1LX6, 824-500MLCA

Application of the substance / the mixture Electronics cleaner

Uses advised against Not for use on monitor screens or glass with anti-glare coatings

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)

1210 Corporate Drive

Burlington, Ontario L7L 5R6

CANADA

+(1) 800-340-0772

+(1) 905-331-1396

info@mgchemicals.com

Distributor:

Masline

511 Clinton Ave S

Rochester, New York 14620

United States

+(1) 586-546-5373

Information department: sds@mgchemicals.com

Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA-Call 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

Classification of the substance or mixture

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category 3
H336 May cause drowsiness or dizziness.

Label elements

GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Propan-2-ol

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof equipment.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist, vapors or spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, and eye protection or face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, and national regulations.

· **Other hazards** Repeated exposure may cause skin dryness or cracking.

3 Composition/Information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

67-63-0 Propan-2-ol

· **Identification number(s)**

· **EC number:** 200-661-7

(Contd. on page 3)



Safety Data Sheet
according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 2)

· Index number: 603-117-00-0

· **Dangerous components:**

67-63-0	Propan-2-ol	99.7% w/w
---------	-------------	-----------

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.

· **After skin contact:**

Take off immediately all contaminated clothing.
Wash with plenty of soap and water.

· **After eye contact:**

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.

· **After swallowing:**

Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture**

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

Prevent fire-fighting wash from entering waterway or sewer system.

· **Hazardous combustion products:** Carbon Oxides (CO_x)

· **Advice for firefighters**

· **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

—CA—

(Contd. on page 4)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Trade name: 824

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation
 - Remove or keep away all sources of extreme heat or open flames.
 - Avoid breathing mist, spray, or vapors.
- **Environmental precautions:**
 - Dilute with plenty of water.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Collect liquid in a sealable, chemical-resistant container.
 - Wash residue with a paper towel and place dirty towels in container.
 - Use soap and water to remove the last traces of residue.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
 - Wear protective gloves and eye protection.
 - Wash hands and exposed skin thoroughly after handling.
 - Take off contaminated clothing and wash it before reuse.
 - Avoid breathing mist, spray, or vapors.
 - Use only outdoors or in a well-ventilated area.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Use explosion-proof apparatus / fittings and spark-proof tools.
 - Ground and bond container and receiving equipment.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Keep in a dry and clean area, away from incompatible substances
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Store locked up.

(Contd. on page 5)

Safety Data Sheet
according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 4)

· **Specific end use(s)** See section 1.2

8 Exposure controls/ Personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-63-0 Propan-2-ol	
EL (Canada)	STEL: 400 ppm TWA: 200 ppm
EV (Canada)	STEL: 400 ppm TWA: 200 ppm
PEL (USA)	TWA: 980 mg/m ³ , 400 ppm
REL (USA)	STEL: 1225 mg/m ³ , 500 ppm TWA: 980 mg/m ³ , 400 ppm
TLV (USA)	STEL: 984 mg/m ³ , 400 ppm TWA: 491 mg/m ³ , 200 ppm BEI, A4

· **Ingredients with biological limit values:**

67-63-0 Propan-2-ol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

· **Additional information:**

The lists that were valid during the creation were used as basis.
 Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
 Advice should be sought from respiratory protection specialists.
 If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

(Contd. on page 6)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Trade name: 824

(Contd. of page 5)

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses or tightly sealed goggles: EN 166

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· Physical state	Liquid
· Form:	Low viscosity
· Color:	Colorless
· Odor:	Alcohol-like
· Melting point/Melting range:	-89.5 °C (-129.1 °F)
· Boiling point/Boiling range:	82 °C (179.6 °F)
· Flammability:	Highly flammable.
· Explosion limits:	
· Lower:	2 Vol %
· Upper:	12 Vol %
· Flash point:	12 °C (53.6 °F)
· Auto igniting:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic at 20 °C (68 °F):	2.43 mPas
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.

(Contd. on page 7)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 6)

· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
· Density at 20 °C (68 °F):	0.785 g/cm ³ (6.5508 lbs/gal)
· Relative density at 25 °C (77 °F):	0.785
· Vapor density (air=1):	2.1
· Particle characteristics	Not applicable
· Other information	
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Organic solvents:	99.70 %
· VOC content:	99,700 %
	997.0 g/l / 8.32 lb/gal
· Solids content:	0.3 %
· Evaporation rate	1.5 (ButAc=1)

10 Stability and reactivity

- **Reactivity** At elevated temperatures, may react with aluminum and generate hydrogen gas.
- **Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.
- **Incompatible materials:**
Strong oxidizing agents
Strong acids
Strong bases
Halogenated compounds
Aluminum at temperatures ≥ 49 °C
- **Hazardous decomposition products:**
No dangerous decomposition products known.
Hazardous combustion products: see section 5.

— CA —
(Contd. on page 8)

Safety Data Sheet
 according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 7)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-63-0 Propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/L (rat)

· Primary irritant effect:

· on the eye: Irritating effect.

· Summary of effects and symptoms by route of exposure

· Eyes:

pain
 redness, serious irritation
 tearing of the eyes

· Skin:

redness, may cause mild irritation
 dry skin

· Inhalation:

headache
 narcotic effects
 weakness
 dizziness or drowsiness

· Swallowed: see inhalation symptoms

· Delayed and immediate effects as well as chronic effects from short and long-term exposure

Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

· Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
	3
· NTP (National Toxicology Program)	
Substance is not listed.	

12 Ecological information

· Toxicity

· Aquatic toxicity:

67-63-0 Propan-2-ol	
EC50/ 24 h	5,102 mg/L (daphnia)
EC50/ 72 h	>2,000 mg/L (algae)

(Contd. on page 9)

Safety Data Sheet
according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 8)

LC50 96h	9,640 mg/L (minnow)
----------	---------------------

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** This material and its container must be disposed of as hazardous waste.
- **Uncleaned packagings:**
 - **Recommendation:**
 Containers may still present a chemical hazard/ danger when empty.
 Dispose of contents in accordance with all local, regional, national, and international regulations.
 Where possible retain label warnings and SDS and observe all notices pertaining to the product.
 - **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT/TDG, IMDG, IATA	UN1219
· UN proper shipping name	
· DOT/TDG	Isopropanol
· IMDG	ISOPROPANOL (ISOPROPYL ALCOHOL)
· IATA	Isopropanol (isopropyl alcohol)
· Transport hazard class(es)	
· DOT/TDG (Transport dangerous goods):	
	
· Class	3 Flammable liquids

(Contd. on page 10)

Safety Data Sheet
according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 9)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT/TDG, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
 Limited Quantity	
824-100ML, 824-100MLCA, 824-500ML, 824-500MLCA, 824-1L, 824-1IX6, 824-1LCA	
· DOT/TDG	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Special precautions for user	Not applicable.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· UN "Model Regulation":	UN 1219 ISOPROPANOL, 3, II

—CA—

(Contd. on page 11)



Safety Data Sheet
according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 10)

*** 15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **OSHA Hazard Communication Standard (29 CFR Part 1900)**

The safety data sheet and label comply with HCS 2024.

· **Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· **Sara**

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is listed.

· **TSCA (Toxic Substances Control Act):**

ACTIVE

· **Hazardous Air Pollutants**

Substance is not listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **TLV (Threshold Limit Value)**

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

Substance is listed.

· **Canadian Non-Domestic Substances List (NDSL)**

Substance is not listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

Substance is not listed.

(Contd. on page 12)



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 08/28/2025

Version number 7.02

Revision: 08/28/2025

Trade name: 824

(Contd. of page 11)

· Canadian Ingredient Disclosure list (limit 1%)
Substance is listed.

· HMIS-ratings (scale 0 - 4)

Health = 1
Fire = 3
Reactivity = 0

· Europe

· RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

· Per- and polyfluoroalkyl substances (PFAS)
Substance is not listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Regulatory department

· Contact: sds@mgchemicals.com

· Date of previous version 10/25/2024

· Version number of previous version: 7.01

· Date of preparation 08/28/2025

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety

· * Data compared to the previous version altered.