

## 1. Identification

**Product identifier** Lacquer Touch-up Paint - Clear Topcoat

**Other means of identification**  
**FIR No.** 039975

**Recommended use** Automotive exterior touch-up paint

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company Name** Ford Motor Company

**Address** Attention: SDS Information, P.O. Box 1899  
 Dearborn, Michigan 48121  
 USA

**Telephone** 1-800-392-3673

**SDS Information** 1-800-448-2063 (USA and Canada)  
 fordsds.com

**Emergency telephone numbers**

Poison Control Center: USA and Canada: 1-800-959-3673  
 INFOTRAC (Transportation): USA and Canada 1-800-535-5053

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity (fertility, the unborn child)	Category 1B
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
<b>Environmental hazards</b>	Specific target organ toxicity, repeated exposure	Category 2
	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility. May damage the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

### Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

May cause an allergic skin reaction.

### Supplemental information

56% of the mixture consists of component(s) of unknown acute dermal toxicity. 24% of the mixture consists of component(s) of unknown acute inhalation toxicity.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
TOLUENE		108-88-3	37
BUTANONE		78-93-3	14
4-METHYLPENTAN-2-ONE		108-10-1	8
ETHANOL		64-17-5	6
BENZYL BUTYL PHTHALATE		85-68-7	5
CYCLOHEXANE		110-82-7	2

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Avoid contact with eyes, skin, and clothing. Do not breathe mist/vapors. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Pregnant or breastfeeding women must not handle this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin, and clothing. Do not breathe mist/vapors. Avoid prolonged exposure. When using, do not eat, drink or smoke. Do not taste or swallow. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Use non-sparking tools and explosion-proof equipment. Explosion-proof general and local exhaust ventilation. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Should be handled in closed systems, if possible. Avoid release to the environment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS.

**Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
4-METHYLPENTAN-2-ONE (CAS 108-10-1)	PEL	410 mg/m3

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
BUTANONE (CAS 78-93-3)	PEL	100 ppm
		590 mg/m3
CYCLOHEXANE (CAS 110-82-7)	PEL	200 ppm
		1050 mg/m3
ETHANOL (CAS 64-17-5)	PEL	300 ppm
		1900 mg/m3
		1000 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
4-METHYLPENTAN-2-ONE (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
BUTANONE (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
CYCLOHEXANE (CAS 110-82-7)	TWA	100 ppm
ETHANOL (CAS 64-17-5)	STEL	1000 ppm
TOLUENE (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
4-METHYLPENTAN-2-ONE (CAS 108-10-1)	STEL	300 mg/m3
		75 ppm
		205 mg/m3
BUTANONE (CAS 78-93-3)	TWA	50 ppm
		885 mg/m3
		300 ppm
CYCLOHEXANE (CAS 110-82-7)	TWA	590 mg/m3
		200 ppm
		1050 mg/m3
ETHANOL (CAS 64-17-5)	TWA	300 ppm
		1900 mg/m3
TOLUENE (CAS 108-88-3)	STEL	1000 ppm
		560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
4-METHYLPENTAN-2-ONE (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BUTANONE (CAS 78-93-3)	2 mg/l	MEK	Urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

TOLUENE (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

TOLUENE (CAS 108-88-3)

Skin designation applies.

**Appropriate engineering controls**

Provide eyewash station and safety shower. Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, appropriate local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Suitable chemical protective gloves should be worn when the potential exists for skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile or neoprene gloves are recommended.

**Other**

Wear appropriate chemical resistant clothing if applicable.

**Respiratory protection**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Clear.

**Odor**

Hydrocarbon-like.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

170.6 °F (77 °C)

**Flash point**

35.6 °F (2.0 °C) Pensky-Martens Closed Cup

**Evaporation rate**

6.1 (BuAc=1)

**Flammability (solid, gas)**

Not applicable.

**Upper/lower flammability or explosive limits****Explosive limit - lower (%)**

1 %

**Explosive limit - upper (%)**

19 %

**Vapor pressure**

100 mm Hg (@ 20 °C)

Vapor density	1.5 (Air=1)
Relative density	0.9
<b>Solubility(ies)</b>	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	> 20.5 cSt
Viscosity temperature	104 °F (40 °C)
<b>Other information</b>	
Heat of combustion	22.92 kJ/g
VOC	5.27 lb/gal

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Amines. Ammonia. Caustics. Isocyanates.
<b>Hazardous decomposition products</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Information on toxicological effects

#### Acute toxicity

Components	Species	Calculated/Test Results
4-METHYLPENTAN-2-ONE (CAS 108-10-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 16000 mg/kg
<b>Inhalation</b>		
LC50	Rat	8.2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2080 mg/kg
<b>Other</b>		
LD50	Guinea pig	0.919 ml/kg
	Mouse	590 mg/kg
	Rat	1.14 ml/kg

Components	Species	Calculated/Test Results
BUTANONE (CAS 78-93-3)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 8000 mg/kg
<b>Inhalation</b>		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
<b>Oral</b>		
LD50	Mouse	670 mg/kg
	Rat	4500 - 6800 mg/kg 2300 - 3500 mg/kg
<b>Other</b>		
LD50	Mouse	1660 g/kg, 24 Hours
	Rat	12290 mg/kg, 24 Hours
CYCLOHEXANE (CAS 110-82-7)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
NOEL	Monkey	1243 ppm, 6 Hours
<b>Oral</b>		
LD50	Mouse	1300 mg/kg
	Rat	29820 mg/kg
ETHANOL (CAS 64-17-5)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Mouse	39 mg/l, 4 Hours
	Rat	20000 ppm, 10 Hours
<b>Oral</b>		
LD50	Dog	5.5 g/kg
	Guinea pig	5.6 g/kg
	Mouse	3450 mg/kg
	Rat	7060 mg/kg 17.8 g/kg 11.5 g/kg 10.6 g/kg 9.9 g/kg 6.2 g/kg
<b>Other</b>		
LD50	Mouse	8285 mg/kg 1973 mg/kg 933 mg/kg
	Rat	3750 mg/kg 1440 mg/kg
TOLUENE (CAS 108-88-3)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12120 mg/kg 14.1 ml/kg

Components	Species	Calculated/Test Results
<b>Inhalation</b>		
LC50	Mouse	5320 ppm, 8 Hours
		400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	5000 mg/kg
		2.6 g/kg
<b>Other</b>		
LD50	Mouse	2250 mg/kg
		640 mg/kg
		59 mg/kg
	Rat	1.15 g/kg
		1960 mg/kg
		1332 mg/kg
		1.64 g/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Suspected of causing cancer.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
	4-METHYLPENTAN-2-ONE (CAS 108-10-1)	2B Possibly carcinogenic to humans.
<b>Reproductive toxicity</b>	Possible reproductive hazard. May damage fertility. May damage the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. Respiratory system. May cause drowsiness and dizziness. Central nervous system.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure. Liver. Urinary system. Heart. Vascular system. Reproductive organs.	
<b>Aspiration hazard</b>	Not an aspiration hazard.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.	

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

### Ecotoxicity

Components	Species	Calculated/Test Results
4-METHYLPENTAN-2-ONE (CAS 108-10-1)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 492 - 593 mg/l, 96 hours
BENZYL BUTYL PHTHALATE (CAS 85-68-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 0.9 - 1.1 mg/l, 48 hours
Fish	LC50	Shiner perch ( <i>Cymatogaster aggregata</i> ) 0.47 - 0.56 mg/l, 96 hours

Components	Species	Calculated/Test Results
<b>BUTANONE (CAS 78-93-3)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)
4025 - 6440 mg/l, 48 hours		
> 400 mg/l, 96 hours		
<b>CYCLOHEXANE (CAS 110-82-7)</b>		
<b>Aquatic</b>		
Fish	LC50	Striped bass (Morone saxatilis)
8.3 mg/l, 96 hours		
<b>ETHANOL (CAS 64-17-5)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Fathead minnow (Pimephales promelas)
7.7 - 11.2 mg/l, 48 hours		
> 100 mg/l, 96 hours		
<b>TOLUENE (CAS 108-88-3)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
5.46 - 9.83 mg/l, 48 hours		
5.89 - 7.81 mg/l, 96 hours		

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

4-METHYLPENTAN-2-ONE	1.31
BENZYL BUTYL PHTHALATE	4.91
BUTANONE	0.29
CYCLOHEXANE	3.44
ETHANOL	-0.31
TOLUENE	2.73

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
D018: Waste Benzene  
D035: Waste Methyl ethyl ketone  
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3

**Subsidiary risk** -  
**Label(s)** 3  
**Packing group** II  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IATA

**UN number** UN1263  
**UN proper shipping name** Paint  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

**UN number** UN1263  
**UN proper shipping name** Paint  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** Not available.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

#### DOT



#### IATA; IMDG



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** All components of the mixture on the TSCA 8(b) inventory are designated "active".

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### TSCA Chemical Action Plans, Chemicals of Concern

BENZYL BUTYL PHTHALATE (CAS 85-68-7)

Phthalates Action Plan

**CERCLA Hazardous Substance List (40 CFR 302.4)**

4-METHYLPENTAN-2-ONE (CAS 108-10-1)	Listed.
BENZYL BUTYL PHTHALATE (CAS 85-68-7)	Listed.
BUTANONE (CAS 78-93-3)	Listed.
CYCLOHEXANE (CAS 110-82-7)	Listed.
ETHANOL (CAS 64-17-5)	Listed.
TOLUENE (CAS 108-88-3)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

<b>Classified hazard categories</b>	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity (single or repeated exposure)
-------------------------------------	---

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
4-METHYLPENTAN-2-ONE	108-10-1	8
CYCLOHEXANE	110-82-7	2
TOLUENE	108-88-3	37

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

4-METHYLPENTAN-2-ONE (CAS 108-10-1)  
TOLUENE (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

**US state regulations****California Proposition 65**

**WARNING:** This product can expose you to chemicals including 4-METHYLPENTAN-2-ONE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

4-METHYLPENTAN-2-ONE (CAS 108-10-1) Listed: November 4, 2011

**California Proposition 65 - CRT: Listed date/Developmental toxin**

4-METHYLPENTAN-2-ONE (CAS 108-10-1) Listed: March 28, 2014

**International Inventories**

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	06-27-2019
<b>Version</b>	01
<b>HMIS® ratings</b>	Health: 2 Flammability: 3 Physical hazard: 0
<b>NFPA ratings</b>	Health: 2 Flammability: 3 Instability: 0

**Preparation Information and  
Disclaimer**

This document was prepared by FCSD-Toxicology, Ford Motor Company, Fairlane Business Park IV, 17225 Federal Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

**Part number(s)**

PMP-19500-XXXXA