

		Page: 1
SAFETY DATA SHEET		Revision Date: 01/26/2019
		Print Date: 1/31/2019
		SDS Number: R0367943
MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 773775		Version: 1.13

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-	72623-87-1	Asp. Tox. 1; H304	>=80.00 - < 90.00



SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 773775

Based			
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.50 - < 5.00
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8	Skin Sens. 1; H317	>=0.10 - < 0.50

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
- Specific extinguishing methods :
Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 773775

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Wear as appropriate:
Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: mild
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: > 424 °F / 218 °C (1013 hPa)
Flash point	: 394 - 480 °F / 201 - 249 °C Method: Cleveland open cup
Evaporation rate	: < 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 1 hPa Calculated Vapor Pressure
Relative vapour density	: > 1 AIR=1
Relative density	: No data available
Density	: 0.8518 g/cm ³ (60.01 °F / 15.56 °C)

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Solubility(ies)
Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-
octanol/water : No data available
Decomposition temperature : No data available
Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : 28.8 mm²/s (104 °F / 40 °C)
Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under recommended storage conditions.
Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.
Conditions to avoid : excessive heat
Incompatible materials : alkalis
Strong acids
Strong oxidizing agents
Hazardous decomposition
products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation
under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

DODECYL HYDROXYPROPYL SULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal
absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Components:**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Species : Rabbit
Result : No skin irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation
Remarks : Expected based on components.

Remarks : Unlikely to cause eye irritation or injury.

Components:**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Species : Rabbit
Result : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 773775

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit
 Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type : Buehler Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.

DODECYL HYDROXYPROPYL SULFIDE:

Test Type : Local lymph node assay
 Species : Guinea pig
 Assessment : May cause sensitisation by skin contact.
 Method : OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Genotoxicity in vitro : Test Type: Ames test
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
 Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
 Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubilityToxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 773775

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

DODECYL HYDROXYPROPYL SULFIDE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Method: OECD Test Guideline 203
 GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.58 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF

M-Factor (Short-term (acute) aquatic hazard) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia magna (Water flea)): 0.32 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Method: OECD Test Guideline 211
 GLP: yes

M-Factor (Long-term (chronic) aquatic hazard) : 1

Persistence and degradability
Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:
 Biodegradability : Result: Not readily biodegradable.



SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

DODECYL HYDROXYPROPYL SULFIDE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Partition coefficient: n- : log Pow: 4.7 - 6.5
octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information : unprofessional handling or disposal., Harmful to aquatic life
with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and
federal regulations.

The product should not be allowed to enter drains, water
courses or the soil.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION



SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 773775

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MX_DG

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TDG_INWT_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

**SAFETY DATA SHEET**

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943

Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
773775

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
BENZENE	71-43-2	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFUR DIOXIDE	7446-09-5	500	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

SAFETY DATA SHEET

Revision Date: 01/26/2019

Print Date: 1/31/2019

SDS Number: R0367943


Version: 1.13

MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 773775

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/26/2019

<p>NFPA:</p>  <p>Flammability: 1 Health: 0 Instability: 0 Special hazard.</p>	<p>HMIS III:</p> <table border="1"> <tr> <td>HEALTH</td> <td>0</td> </tr> <tr> <td>FLAMMABILITY</td> <td>1</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td>0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

	Page: 15
SAFETY DATA SHEET	Revision Date: 01/26/2019
	Print Date: 1/31/2019
	SDS Number: R0367943
MaxLife™ DEX/MERC Synthetic Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 773775	Version: 1.13

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System